

96271768 VIOO 1L120 830 ANT

LED 5W LED_VIOO_3K	IP65	IK10	⏏	CE	⚡	EAC	⚡	⚡	⚡
--------------------	------	------	---	----	---	-----	---	---	---


Vioo

Small LED floodlight for window surround illumination. 1 LED driven at a constant 1.2A. Body: die-cast aluminium (AB47100) with high corrosion resistance, painted dark grey. Front lens: polycarbonate. Class I electrical, IP65, IK10. Pre-wired with 1,5m H05-RNF cable. Complete with 3000K LED


Dimensions: 150 x 90 x 40 mm
 Luminaire input power: 4.7 W
 Luminaire luminous flux: 151 lm
 Luminaire efficacy: 32 lm/W
 Weight: 0.71 kg



TLG_VIOO_F_PDB.jpg



TLG_VIOO_M_LD1.wmf



TLLA_VIOO3K_DC.ltd

Lamp position: STD - standard
 Light Source: LED
 Luminaire luminous flux*: 151 lm
 Luminaire efficacy*: 32 lm/W
 Colour Rendering Index min.: 80
 LOR: 1,00 ULOR: 1,00 DLOR: 0,00

Correlated colour temperature: 3000 Kelvin
 Rated median useful life*:
 50000h at 25°C
 Ballast: 1x EL2
 Luminaire input power*: 4.7 W Power factor = 0.6
 Dimming: FO

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
 © Thorn Lighting