

VISTA FLEX LX


VISTA FLEX LX L30 930 SD WH FRO END 67

21052403


Vista Flex, 3m, 90CRI 3000K, Side bend, White, Front entry, End of run, IP67

Vista Flex Lx is a flexible linear marker luminaire delivering 1038 lm with 90CRI 3000K LEDs. Vista Flex Lx is rated to IP67. This variant is Side bend with Front entry and is End of run. Luminaire utilizes 30 W of power and efficacy of 34.6 lm/W. Designed to $\{\{tm21_reported_median_25\}\}$, the product is tested to LM79 standards by an independent UKAS accredited laboratory. LEDs are binned to a 2 step MacAdam ellipse. The fitting is 3000 x 12 x 20 mm and weighs 1.32 kg. The product is designed to be installed in ambient temperature -20°C to +45°C. The fixture is powered by a remote constant voltage driver and optional dimming unit (to be ordered separately).

DIMENSIONS (MM)



POLAR PLOT



- Light Source: LED
- Luminaire luminous flux: 1038 lm
- Luminaire efficacy: 34.6 lm/W
- Colour rendering index min: 90CRI
- Correlated colour temperature: 3000K
- Chromaticity tolerance (Initial MacAdam): 2 step MacAdam ellipse
- TM-21 Reported median useful life @ 50°C: N/A
- Luminaire input power: 30 W

APPROVALS

IP67